

Calor recommend the following single stage regulator be used with all propane cylinders:

Incorporating a Consumer Safety Over Pressure Device with Reset (OPSO) CSR 485 Low Pressure 37mb Propane Cylinder Regulator 4kg/h (55kW)



Low pressure cylinder regulator fitted with the latest Consumer Safety Protection (OPSO)

- New LPG safety system including Consumer Safety Reset (CSR) and Over Pressure Shut Off (OPSO*) developed by Clesse enables the consumer to reset the regulator should the gas pressure exceed recommended limits, protecting appliances and property.
- Clear visible indication and resetting is performed by a "Push to reset" system, similar to electrical consumer RCD protection.
- Ideal for all types of LPG Propane cylinder applications Domestic, Commercial, Holiday and Park Homes.

Model No.	CSR 485
Capacity	4kg/h- 55kW - (187,500Btu/hr)
Operating Pressure	37mb (preset)
Cylinder Connection	Irish Propane Nut
Outlet Connection	1/2" BSP Female
Pressure Relief Valve (PRV) setting	75mb
CSR OPSO Setting	125mb
Manufactured in	France
EN Standards	BSEN 16129: 2013

Available from Hamilton Gas Products & Southern Gas Installations.

CALOR CONTACT INFORMATION:

ROI: 1850 812 450 NI: 028 9045 5588 calorgas.ie



CG - SF - CED - 021 Rev.1